



VALVTECT® X-TENDED PROTECTION+™ GASOLINE TREATMENT with Rapid Clean-Up Technology (GATC08)

ValvTect® X-Tended Protection+™ Gasoline Treatment with Rapid Clean-Up Technology is specially formulated to quickly clean-up gum, varnish, and all types of fuel system deposits to improve efficiency and prevent fuel related problems caused by deposits and "gunk."


ValvTect® X-Tended Protection+™ Gasoline Treatment with Rapid Clean-Up Technology helps gasoline powered engines operate at "Beyond Top Tier" performance. ValvTect's sophisticated detergent package is test proven to quickly clean-up Gasoline Direct Injection (GDI) and Port Fuel Injection (PFI) deposits and keeps the engine & fuel system "super clean" & in "like new" condition. It also cleans up and prevents gum and varnish build up. Continued use can maximize power and performance, optimize fuel economy, lower maintenance costs, and reduce harmful exhaust emissions.

Product performance has been documented by ASTM and SAE with both ethanol & ethanol free grades of gasoline. ValvTect X-tended Protection+™ with Rapid Clean-Up technology is test proven to clean up deposits in all types of gasoline engines (including PFI and GDI). It has been tested extensively in BMW, Honda, GM, Ford, Mercedes Benz, VW & Yamaha engines. ValvTect's X-tended Protection+™ Rapid Clean-Up Gasoline Treatment is an effective and economical option to maximize performance and prevent fuel related problems.

FEATURES AND BENEFITS

- **Rapidly cleans up fuel injectors, carburetors, intake valves, intake port and manifold deposits.**
- **Helps prevent combustion chamber deposits.**
- **Stops rough idling.**
- **Improves engine power, acceleration & performance*.**
- **Restores power & performance*.**
- **Reduces fuel consumption*.**
- **Prevents fuel filter plugging and extends fuel filter life.**
- **Cleans-up harmful gum and varnish residues in gasoline fuel systems and prevents build-up.**
- **Documented to meet ASTM, SAE, and NACE corrosion test specifications.**
- **Tested extensively in all types of gasoline engines.**
- **Suitable for all types of gasoline including recreational grade (non-ethanol), ethanol blends up to E85, and other alternative gasoline types. Safe for all 2 cycle & 4 cycle gasoline engines.**
- **8 ounces treats up to 40 gallons, 1 ounce treats 5 gallons.**

* Based on clean-up of fuel system deposits.



PRODUCT DATA SHEET

VALVTECT® X-TENDED PROTECTION+™ GASOLINE TREATMENT with Rapid Clean-Up Technology (GATC08)

APPLICATIONS

This high performance gasoline additive is a very effective multifunctional treatment that can be used to clean up the fuel system and maximize gasoline performance. It can be easily blended into all types of gasoline including recreational grade (non-ethanol), ethanol fuels (up to E85), and other alternative gasoline types. This product is specially formulated for use in all types of 2 & 4 cycle gasoline engines and applications. This includes passenger, heavy-duty, high performance, marine, agriculture, motorcycle, lawn equipment, stand-by generators & other gasoline engines. This product does not replace the need for 2-cycle oil. This premium product may be used in all automotive & other gasoline engines where improved performance, and improved engine cleanliness is desired.

BLENDING RECOMMENDATIONS

Product should be added to the fuel storage tank prior to adding fuel. Storage tank should have a 20% heel of gasoline & be free of excess water and/or sludge.

Treat Rate

1oz : 5 gallons

8oz : 40 gallons

SAFETY PRECAUTIONS

When handling this product, persons should exercise caution and wear protective goggles, gloves and clothing. See cautions indicated in the corresponding Safety Data Sheet before handling and storing this product.

WARRANTY

We guarantee this product to comply with our published specifications. Since the use of this product is beyond our control, we disclaim responsibility for its performance, handling, use, storage, the results obtained, or any injury of any nature resulting there from. Product warrantee and seller's obligations apply only to replacement of product. Seller assumes no liability for any claim or loss of any other kind. In no event shall seller be liable for indirect punitive, special or consequential damages or expenses. Any warrantee claim shall be governed by and construed in accordance with the laws and jurisdiction of the State of North Carolina.

TYPICAL SPECIFICATIONS

Color (ASTM D1544)	5
Specific Gravity @ 60° F.....	0.8740
Density, lbs./gal. (approx.).....	7.28
Flash Point °F, PMCC	104
Additive Pour Point °F.....	<-50
Viscosity @ 77° F cSt.....	N/A



Warning: Cancer – www.p65warnings.ca.gov

PACKAGING

Available in 12/08 oz bottles per case.

