FEATURES & BENEFITS	Diesel Guard™ Anti-Gel Deicer Concentrate (AGPW)	Diesel Guard™ Biodiesel Anti-Gel Deicer (BDAGDW)	Diesel Guard™ Supreme Plus Winter (DGSPW)	Diesel Guard™ Supreme Winter XP (DGSWXP)
Standard Treat Rate (Gallons)	1:3000	1:1500*	1:1500	1:1500
Helps prevent gelling & icing	1	<b>✓</b>	<b>✓</b>	<b>√√</b>
Cold flow improvers to increase cold weather operability				<b>//</b>
Contains VT330A™ reducing Cold Filter Plug Point (CFPP)		<b>✓</b>	<b>✓</b>	11
Reduces pour point	<b>/</b>		<b>✓</b>	<b>1</b>
Contains wax crystal modifiers	<b>✓</b> )	<b>✓</b>	1	1
Contains heavy wax crystal modifiers for up to B20 biodiesel blends & hard to treat fuels				
Provides wax anti-settling protection (WASA)		<b>✓</b>	<b>√</b> 100 h	<b>√</b> √
Contains non-alcohol SMART deicer		1		
Cleans up Internal & External Deposits (IDID)				1
Prevents sticky & fouled injectors				
Prevents formulation of asphaltene deposits & sludge	P 1996			<b>✓</b>
Meets DW10 & XUD9 clean up/ keep clean performance specs				1
Restores/improves fuel efficiency up to 7.3%	<b>\</b> 法信气			<b>✓</b>
Extends fuel filter life			1	4/1
Cetane booster to improve cold starts and reduce black smoke	为人类		11	<b>√</b>
Contains VT101™ lubricity improver preventing premature wear of fuel injectors & pumps				
Contains corrosion inhibitor				<b>✓</b>
Disperses controlled amounts of water		1	1	W.



\* 1:1500 gallon treat rate for up to B10 blends, 1:750 treat rate for up to B20 blends

√√ additional additive for increased performance