

Safety Data Sheet

1. Identification

Product Information. GAAIBK

Product Name: XP+ GASOLINE ALL IN ONE

Recommended Use. Additive concentrate

Uses advised against. Read label instructions and SDS

Supplier. ValvTect Petroleum Products

A Division of Modern Recreational Technologies, Inc.

2220 Highway 70 SE., Suite 100

Hickory, NC 28602 800-728-8258

Emergency telephone number. Chemtrec: +1-800-424-9300 USA

Chemtrec: +1 703-527-3887 ex-USA

24 hrs./day, 7 days/week

2. Hazards Identification

GHS Classification in accordance with 29 CFR 1910.1200

Flammable Liquid, category 3 Germ Cell Mutagenicity, category 1B Carcinogenicity, category 1B Reproductive Toxicity, category 1B Acute Toxicity, Inhalation, category 4 Skin Irritation, category 2 Eye Irritation, category 2A Skin Sensitizer, category 1

GHS Pictograms







Signal Word

Danger

Unknown Acute Toxicity

71.2% of the mixture consists of ingredient(s) of unknown acute toxicity

HAZARD STATEMENTS

Flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Harmful if inhaled.

May cause genetic defects.

May cause cancer.

May damage fertility or the unborn child.

Precautionary Statements - Prevention.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, sparks, open flames, hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash face and hands and any exposed skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves, protective clothing, eye protection, face protection

Precautionary Statements - Response.

If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (If applicable, see label for any additional instructions).

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use CO₂ dry chemical or foam to extinguish.

Precautionary Statements - Storage.

Store in a well-ventilated place. Keep cool.

Store locked up.

Precautionary Statements - Disposal.

Dispose of contents in accordance with local, regional, national, international regulations.

3. Composition/Information on Ingredients

| <u>Chemical Name</u> | CAS-No. | <u>Wt. %</u> |
|---|------------|--------------|
| Solvent naphtha (petroleum), light aromatic | 64742-95-6 | 50-75 |
| 1,2,4-TRIMETHYLBENZENE | 95-63-6 | 10-25 |
| Paraffins (petroleum), normal C5-20 | 64771-72-8 | 2.5-10 |
| XYLENE | 1330-20-7 | 2.5-10 |
| Ethylene glycol monobutyl ether | 111-76-2 | 1.0-2.5 |
| Naphtha, petroleum, hydrotreated heavy | 64742-48-9 | 0.1-1.0 |
| Benzene, (1-methylethyl)- | 98-82-8 | 0.1-1.0 |
| 2,6-Di-tert-Butylphenol | 128-39-2 | 0.1-1.0 |
| Ethyl Benzene | 100-41-4 | 0.1-1.0 |

The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid Measures

Description of first-aid measures.

General advice.

Move victim to a safe isolated area. When symptoms persist or in all cases of doubt seek medical advice. Call a poison control center or doctor for treatment advice.

Inhalation.

Move to fresh air. Apply artificial respiration if victim is not breathing. Call a poison control center or doctor for treatment advice.

Skin contact.

Wash off immediately with soap and plenty of water. Remove all contaminated clothes and shoes. Remove and wash contaminated clothing before re-use. Call a poison control center or doctor for treatment advice.

Eye contact.

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a poison control center or doctor for treatment advice.

Ingestion.

Do not induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. If swallowed, call a poison control center or doctor immediately. Gently wipe or rinse the inside of the mouth with water. If a person vomits when lying on his back, place him in the recovery position.

Symptoms.

See Section 2 and Section 11, Toxicological effects for description of potential symptoms.

Notes to physician.

Treat symptomatically.

5. Fire-fighting Measures

Extinguishing media.

Suitable extinguishing media.

Use:. Dry powder. Alcohol-resistant foam. Carbon dioxide (CO₂). Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

Extinguishing media which shall not be used for safety reasons.

Water may be unsuitable for extinguishing fires.

Special hazards arising from the substance or mixture.

Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Air/vapor mixtures may explode when ignited. Containers may explode when heated.

Advice for firefighters.

Cool containers with flooding quantities of water until well after fire is out.

Evacuate personnel to safe areas.

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures.

Personal precautions.

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. All equipment used when handling the product must be grounded. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Wear protective gloves/clothing and eye/face protection. Stop all work that requires a naked flame, stop all vehicles, stop all machines and equipment that may cause sparks or flames. Do not breathe vapors or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Thoroughly decontaminate all protective equipment after use. Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill.

Advice for emergency responders.

Refer to protective measures listed in sections 7 and 8. Use personal protection recommended in Section 8.

Environmental precautions.

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Dike to collect large liquid spills. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

Methods and materials for containment and cleaning up.

Methods for Containment.

Dike to collect large liquid spills. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Ground and bond containers when transferring material. Take precautionary measures against static discharges. Use personal protective equipment. Remove all sources of ignition.

Methods for cleaning up.

Prevent further leakage or spillage if safe to do so. Keep away from open flames, hot surfaces and sources of ignition. Keep in suitable and closed containers for disposal. All equipment used when handling the product must be grounded. Keep combustibles (wood, paper, oil, etc) away from spilled material. Ventilate the area. Use personal protective equipment as required. Shut off ignition sources; including electrical equipment and flames. Clean contaminated objects and areas thoroughly while observing environmental regulations. Never return spills in original containers for re-use.

Reference to other sections.

See section 8 for more information.

7. Handling and Storage

Conditions for safe storage, including any incompatibilities.

Advice on safe handling.

Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Wash hands before breaks and immediately after handling the product. All equipment used when handling the product must be grounded. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Use according to package label instructions. Ground and bond containers when transferring material.

Hygiene measures.

Handle in accordance with good industrial hygiene and safety practice for diagnostics. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Storage Conditions.

Keep container closed when not in use. Keep in properly labeled containers. Keep containers tightly closed in a dry, cool and well-ventilated place. Store in accordance with local regulations. Keep from freezing. Keep away from food, drink and animal feedingstuffs. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

8. Exposure Controls/Personal Protection

| Ingredients with Occupational Exp Chemical Name | ACGIH TLV-TWA | ACGIH-TLV STEL | OSHA PEL-TWA | OSHA PEL-CEILING |
|--|---------------|----------------|--------------|------------------|
| 1,2,4-TRIMETHYLBENZENE | 10 ppm | N.E. | N.E. | N.E. |
| XYLENE | 20 ppm | N.E. | 100 ppm | N.E. |
| Ethylene glycol monobutyl ether | 20 ppm | N.E. | 50 ppm | N.E. |
| Benzene, (1-methylethyl)- | 5 ppm | N.E. | 50 ppm | N.E. |
| Ethyl Benzene | 20 ppm | N.E. | 100 ppm | N.E. |

TLV = Threshold Limit Value TWA = Time Weighted Average PEL = Permissible Exposure Limit STEL = Short-Term Exposure Limit N.E. = Not Established

Engineering Measures.

Ensure adequate ventilation, especially in confined areas. Apply technical measures to comply with the occupational exposure limits.

Personal protective equipment.

Eye/Face Protection.

If splashes are likely to occur, wear:. Face-shield. Safety glasses with side-shields. Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to handling and processing of material. Tightly fitting safety goggles.

Skin and body protection.

Use: Long sleeved clothing. Protective shoes or boots. Solvent-resistant gloves. Solvent-resistant apron and boots. Wear impervious gloves and/or clothing if needed to prevent contact with the material. Gloves must be inspected prior to use. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Remove and wash contaminated clothing before re-use.

Respiratory protection.

In case of inadequate ventilation wear respiratory protection. NIOSH/MSHA approved respiratory protection should be worn if exposure is anticipated. If exposure limits are exceeded or irritation is experienced, respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

41 (105.80)

9. Physical and chemical properties.

Information on basic physical and chemical properties.

Physical state Liquid
Appearance No Information
Color No Information
Odor No Information
Odor Threshold No Information
PH No Information
Melting/freezing point., °C (°F) No Information

Boiling point/boiling range., °C (°F) 161 - 551 (321.8 - 1023.8)

Evaporation rateNo InformationExplosive properties.No InformationVapor pressure.No InformationVapor density.No Information

Specific Gravity. (g/cm³) 0.874

Water solubility.No InformationPartition coefficient.No InformationAutoignition temperature.,°CNo InformationDecomposition Temperature °C.No InformationViscosity, kinematic.No Information

Other information.

Flash Point., °C (°F)

Volatile organic compounds (VOC) content. No Information

Density, lb/gal 7.280

10. Stability and Reactivity

Reactivity.

Stable under normal conditions.

Chemical stability.

Stable under recommended storage conditions. Unstable if heated > 100 deg C / 212 deg F.

Possibility of hazardous reactions.

None known based on information supplied.

Conditions to Avoid.

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Keep away from heat and sources of ignition. Do not freeze.

Incompatible Materials.

None known based on information supplied.

Hazardous Decomposition Products.

Thermal decomposition can lead to release of irritating gases and vapours. Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

11. Toxicological Information

Information on toxicological effects.

Acute toxicity.

Product Information

No Information

The following values are calculated based on chapter 3.1 of the GHS document.

 ATEmix (oral)
 12,079.7 mg/kg

 ATEmix (dermal)
 16,335.4 mg/kg

 ATEmix (inhalation - dust/mist)
 2.40 mg/l

Component Information.

| CAS-No. | Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|------------|---|-----------------|------------------------|--------------------------|
| 64742-95-6 | Solvent naphtha (petroleum), light aromatic | 8400 mg/kg Rat | N.I. | N.I. |
| 95-63-6 | 1,2,4-TRIMETHYLBENZENE | 3280 mg/kg Rat | >3160 mg/kg Rabbit | 18 mg/L Rat (Vapor) |
| 1330-20-7 | XYLENE | 3500 mg/kg Rat | >4350 mg/kg Rabbit | 29.08 mg/L Rat (Vapor) |
| 111-76-2 | Ethylene glycol monobutyl ether | 470 | 2000 | N.I. |
| 64742-48-9 | Naphtha, petroleum, hydrotreated heavy | >6000 mg/kg Rat | >5000 mg/kg Rabbit | N.I. |
| 98-82-8 | Benzene, (1-methylethyl)- | 1400 mg/kg Rat | 1474 mg/kg Rabbit | >3577 ppm Rat (Gas/Mist) |
| 128-39-2 | 2,6-Di-tert-Butylphenol | >5000 mg/kg Rat | >10000 mg/kg Rabbit | N.I. |
| 100-41-4 | Ethyl Benzene | 3500 mg/kg Rat | 15400 mg/kg Rabbit | NA (Dust) |

N.I. = No Information

Skin corrosion/irritation.

SKIN IRRITANT.

Eye damage/irritation.

No Information

Respiratory or skin sensitization.

No Information

Ingestion.

May be harmful if swallowed.

Germ cell mutagenicity.

No Information

Carcinogenicity.

No Information

| CAS-No. | Chemical Name | <u>IARC</u> | <u>NTP</u> | <u>OSHA</u> |
|-----------|---------------------------------|---------------|--|-------------|
| 1330-20-7 | XYLENE | IARC Group 3 | - | - |
| 111-76-2 | Ethylene glycol monobutyl ether | IARC Group 3 | - | - |
| 98-82-8 | Benzene, (1-methylethyl)- | IARC Group 2B | NTP Reasonally Anticipated to be Human Carcinogen | - |
| 100-41-4 | Ethyl Benzene | IARC Group 2B | - | - |

Reproductive toxicity.

No Information

Specific target organ systemic toxicity (single exposure).

No Information

Specific target organ systemic toxicity (repeated exposure).

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard.

No Information

Primary Route(s) of Entry

Inhalation

12. Ecological Information

Toxicity.

0.00% of the mixture consists of ingredient(s) of unknown aquatic toxicity Ecotoxicity effects.

| Chemical Name | Toxicity to algae | Toxicity to fish | Toxicity to daphnia and other aquatic invertebrates |
|--|---|--|---|
| Solvent naphtha (petroleum), light aromatic 64742-95-6 | - | LC50 96 h Oncorhynchus mykiss 9.22 mg/L | EC50 48 h Daphnia magna 6.14 mg/L |
| 1,2,4-TRIMETHYLBENZENE 95-63-6 | - | LC50 96 h Pimephales promelas 7.19 - 8.28 mg/L | EC50 48 h Daphnia magna 6.14 mg/L |
| Paraffins (petroleum), normal C5-20 64771-72-8 | - | LC50 96 h Pimephales promelas >5000 mg/L | - |
| XYLENE 1330-20-7 | - | LC50 96 h Pimephales promelas 13.4 mg/L, LC50 96 h Oncorhynchus mykiss 2.661 - 4.093 mg/L, LC50 96 h Oncorhynchus mykiss 13.5 - 17.3 mg/L, LC50 96 h Lepomis macrochirus 13.1 - 16.5 mg/L, LC50 96 h Lepomis macrochirus 19 mg/L, LC50 96 h Lepomis macrochirus 7.711 - 9.591 mg/L, LC50 96 h Pimephales promelas 23.53 - 29.97 mg/L, LC50 96 h Cyprinus carpio 780 mg/L, LC50 96 h Cyprinus carpio >780 mg/L, LC50 96 h Poecilia reticulata 30.26 - 40. | EC50 48 h water flea 3.82 mg/L, LC50 48 h Gammarus lacustris 0.6 mg/L |
| Ethylene glycol monobutyl ether 111-76-2 | - | LC50 96 h Lepomis macrochirus 1490 mg/L, LC50 96 h Lepomis macrochirus 2950 mg/L | EC50 48 h Daphnia magna >1000 mg/L |
| Naphtha, petroleum, hydrotreated heavy 64742-48-9 | - | LC50 96 h Pimephales promelas 2200 mg/L | - |
| Benzene, (1-methylethyl)- 98-82-8 | EC50 72 h Pseudokirchneriella subcapitata 2.6 mg/L | LC50 96 h Pimephales promelas 6.04 - 6.61 mg/L, LC50 96 h Oncorhynchus mykiss 4.8 mg/L, LC50 96 h Oncorhynchus mykiss 2.7 mg/L, LC50 96 h Poecilia reticulata 5.1 mg/L | EC50 48 h Daphnia magna 0.6 mg/L, EC50 48 h Daphnia magna 7.9 - 14.1 mg/L |
| 2,6-Di-tert-Butylphenol 128-39-2 | - | - | EC50 48 h Daphnia magna 0.45 mg/L |
| Ethyl Benzene 100-41-4 | EC50 72 h Pseudokirchneriella subcapitata 4.6 mg/L, EC50 96 h Pseudokirchneriella subcapitata >438 mg/L, EC50 72 h Pseudokirchneriella subcapitata 2.6 - 11.3 mg/L, EC50 96 h Pseudokirchneriella subcapitata 1.7 - 7.6 mg/L | LC50 96 h Oncorhynchus mykiss 11.0 - 18.0 mg/L, LC50 96 h Oncorhynchus mykiss 4.2 mg/L, LC50 96 h Pimephales promelas 7.55 - 11 mg/L, LC50 96 h Lepomis macrochirus 32 mg/L, LC50 96 h Pimephales promelas 9.1 - 15.6 mg/L, LC50 96 h Poecilia reticulata 9.6 mg/L | EC50 48 h Daphnia magna 1.8 - 2.4 mg/L |

Persistence and degradability.

No data are available on the product itself.

Bioaccumulative potential.

Discharge into the environment must be avoided.

| CAS-No. | Chemical Name | log POW |
|-----------|---------------------------------|-------------|
| 95-63-6 | 1,2,4-TRIMETHYLBENZENE | 3.63 |
| 1330-20-7 | XYLENE | 2.77 - 3.15 |
| 111-76-2 | Ethylene glycol monobutyl ether | 0.81 |
| 98-82-8 | Benzene, (1-methylethyl)- | 3.55 |
| 128-39-2 | 2,6-Di-tert-Butylphenol | 4.5 |
| 100-41-4 | Ethyl Benzene | 3.6 |

Mobility in soil.

No information

Other adverse effects.

No information

13. Disposal Considerations

Waste Disposal Guidance.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

DOT

Shipping Name: Flammable Liquids, n.o.s (Petroleum distillates, 1,2,4 - Trimethylbenzene

Hazard Class: 3 UN/NA Number: 1993 Packing Group: III

Additional Information: EXCEPTION: As per 49 CFR 173.120(b)(2), a flammable liquid with a flashpoint at or above 38°C or

100°F may be reclassed as a combustible liquid for transportation within the U.S. by motor vehicle or rail only. A Combustible Liquid in a non-bulk packaging (less than 450L or 119 gallons) Is not subject

to any of the HazMat regulations.

IMDG

Proper Shipping Name: Flammable Liquids, n.o.s (Petroleum distillates, 1,2,4 - Trimethylbenzene

UN Number: 1993 Packing Group: III

IATA

TCSI

Proper Shipping Name: UN1993 Flammable Liquids, n.o.s (Petroleum distillates, 1,2,4 - Trimethylbenzene

Hazard Class: 3
Packing Group: III

15. Regulatory Information

International Inventories:

TSCA Complies
DSL Complies
DSL/NDSL Complies

EINECS/ELINCS ENCS IECSC KECI PICCS AIIC NZIOC -

TSCA United States Toxic Substances Control Act Section 8(b) Inventory.

DSL Canadian Domestic Substances List.

DSL/NDSL Canadian Domestic Substances List/Canadian Non-Domestic Substances List

EINECS/ELINCS European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances.

ENCS Japan Existing and New Chemical Substances.

IECSC China Inventory of Existing Chemical Substances.

KECL Korean Existing and Evaluated Chemical Substances.

PICCS Philippines Inventory of Chemicals and Chemical Substances.

AllC Australian Inventory of Chemical Substances.

NZIoC New Zealand Inventory of Chemicals.

TCSI Taiwan Chemical Substance Inventory

U.S. Federal Regulations:

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372: .

| Chemical Name | CAS-No. | Weight Percent |
|---------------------------------|-----------|----------------|
| 1,2,4-TRIMETHYLBENZENE | 95-63-6 | 10-25 |
| XYLENE | 1330-20-7 | 2.5-10 |
| Ethylene glycol monobutyl ether | 111-76-2 | 1.0-2.5 |
| Benzene, (1-methylethyl)- | 98-82-8 | 0.1-1.0 |
| Ethyl Benzene | 100-41-4 | 0.1-1.0 |

TOXIC SUBSTANCES CONTROL ACT 12(b):

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:.

Chemical NameCAS-No.2,4,6-Tri-tert-Butylphenol732-26-3

ADDITIONAL INFORMATION

Additional Information - Sxn 15: No Information

CALIFORNIA PROPOSITION 65 CARCINOGENS



WARNING

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

 Chemical Name
 CAS-No.

 Benzene, (1-methylethyl) 98-82-8

 Ethyl Benzene
 100-41-4

 Diethanolamine
 111-42-2

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

No Proposition 65 Reproductive Toxins exist in this product.

16. Other Information

Revision Date: 11/14/2023 Supersedes Date: 10/18/2023

Reason for revision: Substance and/or Product Properties Changed in Section(s):

01 - Product Information

09 - Physical & Chemical Information Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

HMIS Ratings:

| Health: | 2 | Flammability: | 2 | Physical Hazard: | 0 | Personal Protection: | Х |
|------------|------|---------------|---|------------------|---|----------------------|---|
| NFPA Ratio | ngs: | | | | | | |
| Health: | 2 | Flammability: | 2 | Instability: | 0 | Physical & Chemical: | |

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

Product name.: GAAIBK XP+ GASOLINE ALL IN ONE